

MAXAMGROUP^{LTD}

Digital Inverter Generator

«Runs longer, quieter and more efficiently than a classical generator»



Model	MXM1200i	MXM2000i	MXM2600i(E)	MXM3500i(E)
Technical Data				
Frequency (Hz):	50 / 60	50 / 60	50 / 60	50 / 60
Rated AC Output(KW):	1,0	1,7	2,3	3,0
Max. AC Output(KW):	1,1	1,8	2,5	3,1
Rated AC Voltage (V):		100, 120, 220,230, 240		
Power Factor (cosφ):		1,0		
Engine Mode:	144F-1	152F-4	152F-3	157F-1
Type:	Forced Air-cooled, 4-storke,OHV		Forced Air-cooled, 4-storke,OHC	
Displacement(cc):	60	99	125 1	149,5
Bore×Stroke (mm):	44×39.5	52.4×46	52.4×57.8	57.4×57.8
Max. Output (KW/rpm):	1.4 / 5000	2.3 / 4500	3.4 / 5000	4.0 / 5000
Fuel:		Unleaded Gasoline		
Fuel Tank Capacity (L):	3,0	4.1/3.9	7.5/6.3	7.5/6.3
Continuous Operating (hours):	4.8(100% Load)	3.8(100% Load)	5.5/4.6(100% Load)	(4.1/3.4 (100%) Load)
Oil:		SAE 10W-30 Above SJ Grade		
Oil Capacity (L) :	0,35	0,75	0,9	0,9
Ignition System:	CDI	CDI	CDI	CDI
Starting System:	Recoil Starter	Recoil Starter	Recoil Starter(Electric)	Recoil Starter(Electric)
Operating Noise Level (7m) dB:	58	60	62	62

Weight, Packing and Shipping information:

Net Dimension: L×W×H (mm)	448×236×392	525×282×457	614×341× 506	614×341× 506
O-all Dimension: L×W×H (mm)	480×255× 425	555×315× 490	635×360× 530	635×360× 530
Net Weight (kg):	13,5	18,5	33/37	33.5/37.5
Dry weight (kg):	15,0	21,0	37/40	37.5/40.5
20GP/40GP/40HQ:	540/1100/1320	300/612/765	228/456/456	228/456/456
Certificates:	CE, GS, EPA,CARB, PSE		CE, GS, EPA	CE, GS, EPA,CARB
Options:	USB	USB		USB Electric start Digical meter Remote control

More information and certification questions/requests at the following email:

info@maxam-group.com